



Concrete Saw Petrol – Instructions for Use

HireKING

SAFETY FIRST

If you are collecting the equipment for someone else, please make sure this sheet is given to the equipment user to read. This sheet should be given to the site supervisor if the equipment is being hired for commercial use so that the information is available to all users. Before starting any job, be sure to spend a few minutes planning and understanding the hazards and risks of the activity and determining how you will control them to prevent injury or damage.

<p>Note: This safety and instruction sheet is on the main machine only, you will be issued with additional sheets for the attachments you have.</p>	<p>REQUIRED SAFETY EQUIPMENT</p> 
	<p>Starting Procedure</p> <ol style="list-style-type: none">1. Place saw on ground and put one foot on the plastic housing below the main throttle handle2. Turn ignition switch to on3. Close choke for cold start4. Depress the decompression button (if fitted)5. Lock throttle trigger on full by depressing trigger and throttle lock button with thumb6. Hold with one hand at top handlebar7. Pull starter slowly until a slight resistance is felt8. Give short sharp pulls when engine fires or starts open choke9. If engine doesn't continue to run depress the decompression again and re-pull the starter cord10. Once engine is running, release throttle by squeezing and then releasing the throttle trigger11. Allow engine to warm up before starting to cut
<p>Pre-Start Checks and Safety</p> <ul style="list-style-type: none">• Always use water when using diamond blades• Use the correct speed blade.• Diamond Segmented blades are wet only, wet prevents a lot of dust and can prolong the blade wear• Check fuel tank is full 2 Stroke• Ensure correct blade fitted for the job• Check blade is securely fastened and sitting square on the shaft (do not over tighten)• Ensure all guards are fitted and secure• If cutting dry wear, a dust mask• Have water or extinguisher available in flammable environments• Do not use broken or bent blades• Have a clear work area• Keep people not involved well clear• Beware of loose clothing and oil or grease on hand grips• Quick cut saws are prohibited from use for cutting any cement fibre products which may contain asbestos• When cutting walls, roadways and paths, check first for wires, pipes etc	<p>When Operating</p> <ul style="list-style-type: none">• Always hold saw firmly with both hands• Use a little downward pressure when cutting but not too much• If engine is revving and the blade isn't turning, then you have too much downward pressure or the blade isn't straight in the cut (this can cause the drive belt to burn out)• Release pressure when coming to the end of a cut• Periodically check fuel• Periodically clean air filter <p>Stopping and After Use</p> <ol style="list-style-type: none">1. Allow engine to idle and cool down2. Move ignition switch to off
<p>CONTACT US</p> <p>If you are having any difficulties with this piece of machinery/equipment, please contact us immediately on 0800 30 30 20 follow the options to General Hire.</p>	